

# DATA SHEET

**3E9**

Preliminary material specification

Supersedes data of February 2002

2004 Sep 01




3E9 SPECIFICATIONS

A high permeability material optimized for small toroids used in miniaturized wideband transformers and delay lines.

	CONDITIONS	VALUE <sup>(1)</sup>	UNIT
$\mu_i$	25 °C; $\leq 10$ kHz; 0.25 mT	$20000 \pm 20\%$	
B	25 °C; 10 kHz; 1200 A/m	$\approx 380$	mT
	80 °C; 10 kHz; 1200 A/m	$\approx 210$	
$\tan\delta/\mu_i$	25 °C; 10 kHz; 0.25 mT	$\leq 10 \times 10^{-6}$	
	25 °C; 30 kHz; 0.25 mT	$\leq 50 \times 10^{-6}$	
$\eta_B$	25 °C; 10 kHz; 1.5 to 3 mT	$\leq 1 \times 10^{-3}$	T <sup>-1</sup>
$\rho$	DC; 25 °C	$\approx 0.1$	$\Omega\text{m}$
$T_C$		$\geq 100$	°C
density		$\approx 5000$	kg/m <sup>3</sup>

Note

1. Measured on sintered, non-ground ring cores of dimensions  $\varnothing 14 \times \varnothing 9 \times 5$  which are not subjected to external stresses.






Fig.4 Reversible permeability as a function of magnetic field strength.

## Preliminary material specification

3E9




## DATA SHEET STATUS DEFINITIONS

DATA SHEET STATUS	PRODUCT STATUS	DEFINITIONS
Preliminary specification	Development	This data sheet contains preliminary data. Ferroxcube reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.
Product specification	Production	This data sheet contains final specifications. Ferroxcube reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.

## DISCLAIMER

**Life support applications** — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Ferroxcube customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Ferroxcube for any damages resulting from such application.

## PRODUCT STATUS DEFINITIONS

STATUS	INDICATION	DEFINITION
<b>Prototype</b>		These are products that have been made as development samples for the purposes of technical evaluation only. The data for these types is provisional and is subject to change.
<b>Design-in</b>		These products are recommended for new designs.
<b>Preferred</b>		These products are recommended for use in current designs and are available via our sales channels.
<b>Support</b>		These products are <b>not</b> recommended for new designs and may not be available through all of our sales channels. Customers are advised to check for availability.