

Philips Components - a worldwide company

Australia: Philips Components Pty Ltd., HOMEBUSH,
Tel. +61 2 9704 8141, Fax. +61 2 9704 8139

Austria: Österreichische Philips Industrie GmbH, WIEN,
Tel. +43 1 60 101 12 41, Fax. +43 1 60 101 12 11

Belarus: Philips Office Belarus, MINSK,
Tel. +375 172 200 924/733, Fax. +375 172 200 773

Benelux: Philips Nederland B.V., EINDHOVEN, NL,
Tel. +31 40 25 90 772, Fax. +31 40 25 90 777

Brazil: Philips Components, SÃO PAULO,
Tel. +55 11 821 2333, Fax. +55 11 829 1849

Canada: Philips Electronics Ltd., SCARBOROUGH,
Tel. +1 416 292 5161, Fax. +1 416 754 6248

China: Philips Company, SHANGHAI,
Tel. +86 21 6354 1088, Fax. +86 21 6354 1060

Denmark: Philips Components A/S, COPENHAGEN V,
Tel. +45 3329 3333, Fax. +45 3329 3905

Finland: Philips Components, ESPOO,
Tel. +358 9 615 800, Fax. +358 9 615 80510

France: Philips Composants, SURESNES,
Tel. +33 1 4099 6161, Fax. +33 1 4099 6493

Germany: Philips Components GmbH, HAMBURG,
Tel. +49 40 2489-0, Fax. +49 40 2489 1400

Hong Kong: Philips Hong Kong, KOWLOON,
Tel. +852 2784 3000, Fax. +852 2784 3003

India: Philips India Ltd., MUMBAI,
Tel. +91 22 4930 311, Fax. +91 22 4930 966/4950 304

Indonesia: P.T. Philips Development Corp., JAKARTA,
Tel. +62 21 794 0040, Fax. +62 21 794 0080

Ireland: Philips Electronics (Ireland) Ltd., DUBLIN,
Tel. +353 1 7640 203, Fax. +353 1 7640 210

Israel: Rapac Electronics Ltd., TEL AVIV,
Tel. +972 3 6450 444, Fax. +972 3 6491 007

Italy: Philips Components S.r.l., MILANO,
Tel. +39 2 6752 2531, Fax. +39 2 6752 2557

Japan: Philips Japan Ltd., TOKYO,
Tel. +81 3 3740 5135, Fax. +81 3 3740 5035

Korea (Republic of): Philips Electronics (Korea) Ltd., SEOUL,
Tel. +82 2 709 1472, Fax. +82 2 709 1480

Malaysia: Philips Malaysia SDN Berhad,
Components Division, PULAU PINANG,
Tel. +60 3 750 5213, Fax. +60 3 757 4880

Mexico: Philips Components, EL PASO, U.S.A.,
Tel. +52 915 772 4020, Fax. +52 915 772 4332

New Zealand: Philips New Zealand Ltd., AUCKLAND,
Tel. +64 9 815 4000, Fax. +64 9 849 7811

Norway: Norsk A/S Philips, OSLO,
Tel. +47 22 74 8000, Fax. +47 22 74 8341

Pakistan: Philips Electrical Industries of Pakistan Ltd., KARACHI,
Tel. +92 21 587 4641-49, Fax. +92 21 577 035/+92 21 587 4546

Philippines: Philips Semiconductors Philippines Inc.,
METRO MANILA, Tel. +63 2 816 6345, Fax. +63 2 817 3474

Poland: Philips Poland Sp. z o.o., WARSZAWA,
Tel. +48 22 612 2594, Fax. +48 22 612 2327

Portugal: Philips Portuguesa S.A.,
Philips Components: LINDA-A-VELHA,
Tel. +351 1 416 3160/416 3333, Fax. +351 1 416 3174/416 3366

Russia: Philips Russia, MOSCOW,
Tel. +7 95 755 6918, Fax. +7 95 755 6919

Singapore: Philips Singapore Pte Ltd., SINGAPORE,
Tel. +65 350 2000, Fax. +65 355 1758

South Africa: S.A. Philips Pty Ltd., JOHANNESBURG,
Tel. +27 11 470 5911, Fax. +27 11 470 5494

Spain: Philips Components, BARCELONA,
Tel. +34 93 301 63 12, Fax. +34 93 301 42 43

Sweden: Philips Components AB, STOCKHOLM,
Tel. +46 8 5985 2000, Fax. +46 8 5985 2745

Switzerland: Philips Components AG, ZÜRICH,
Tel. +41 1 488 22 11, Fax. +41 1 481 7730

Taiwan: Philips Taiwan Ltd., TAIPEI,
Tel. +886 2 2134 2900, Fax. +886 2 2134 2929

Turkey: Türk Philips Ticaret A.S., UMRANIYE/ISTANBUL,
Tel. +90 216 522 18 00, Fax. +90 216 522 18 14

United Kingdom: Philips Components Ltd., DORKING,
Tel. +44 1306 512 000, Fax. +44 1306 512 345

United States:

- Philips Components, SAN JOSE, CA,
Tel. +1 408 570 5600, Fax. +1 408 570 5700
- Philips Display Components, ANN ARBOR, MI,
Tel. +1 734 996 9400, Fax. +1 734 761 2776

Yugoslavia (Federal Republic of): Philips Components, BELGRADE,
Tel. +381 11 625 344 / +381 11 3341 299, Fax. +381 11 635 777

Internet:

- Advanced Ceramics & Modules: www.acm.components.philips.com
- Display Components: www.philipsdisplay.com

For all other countries apply to:
Philips Components, Building BAE-1, P.O. Box 218, 5600 MD EINDHOVEN,
The Netherlands, Fax. +31 40 27 22 599

COB30 © Philips Electronics N.V. 1999


All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.
The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands 9398 284 10011 Date of release: 10/99



PHILIPS
Let's make things better.

Breaking frontiers with new μ 10 000 ferrite toroids



PHILIPS
Let's make things better.

3E6 Toroids of a New Generation

Philips Components' very high permeability 3E6 ferrite toroids are mainly used in wideband transformers and common-mode chokes. In many of these applications a high inductance combined with a small occupied volume is of key importance.

Toroids, with their closed magnetic circuit in a high permeability ferrite material are ideal for realizing such design targets.

However, reaching a very high permeability in a ferrite often leads to a rather low material resistivity. This results in excessive eddy-currents at elevated frequencies, especially in larger toroids. When these eddy-currents occur, the applied magnetic field is partly cancelled out inside the ferrite core, resulting in a decreased effective permeability. This spoils the cores' permeability and impedance behaviour as a function of frequency.

Continuous research, the use of improved raw materials and well controlled process conditions have led to strong improvements in 3E6 toroids. This new generation of toroids features a permeability (μ) of 10 000 up to 100 kHz (Fig.1), lower eddy-current losses (Fig.2) and a much higher impedance level at frequencies around 1 MHz (Fig.3). In addition, the curve of permeability as a function of temperature shows moderate variations over a broad temperature range (Fig.4).


Results are a better response to high frequency pulses in wideband transformers and more effective damping of harmonics in mains input filters.




Features

- Very high permeability at frequencies up to well over 100 kHz*
- Stable temperature behaviour in the usual operating range
- Comparatively high Tc of more than 130 °C


* For large sizes the influence of eddy current losses can result in a lower cut-off frequency.




Effective permeability as a function of frequency



Eddy-current losses as a function of frequency



Specific impedance as a function of frequency



Permeability as a function of temperature

conventional μ 10000 toroids

new generation μ 10000 toroids

The product range

Type Number	OD	ID	h	core factor	Ve (mm ³)	le (mm)	Ae (mm ²)	AL ± 30% (nH)
TC2.5/1.3/1.3-3E6	2.54±0.13	1.27±0.13	1.27±0.13	7.14	4.29	5.53	0.78	1835
TC2.5/1.5/0.8-3E6	2.5±0.1	1.5±0.1	0.8-0.1	16.4	2.21	6.02	0.37	765
TC2.5/1.5/1-3E6-S	2.5±0.1	1.5±0.1	1.0±0.1	12.3	2.94	6.02	0.489	1020
TC4/2.2/1.1-3E6	4±0.15	2.2±0.1	1.1±0.1	9.55	8.82	9.18	0.961	1315
TC4/2.2/1.6-3E6	4±0.15	2.2±0.1	1.6±0.1	6.57	12.84	9.2	1.4	1915
TC4/2.2/1.8-3E6	4±0.15	2.2±0.1	1.78±0.1	5.9	14.3	9.18	1.56	2130
TC5.8/3.1/3.2-3E6	5.84±0.15	3.05±0.15	3.18±0.15	3.04	55.8	13	4.27	4130
TC6/4/2-3E6	6±0.15	4±0.15	2±0.1	7.75	30.2	15.3	1.97	1620
TC6.3/3.8/2.5-3E6	6.3±0.25	3.8±0.15	2.5±0.15	4.97	46.5	15.2	3.06	2530
TC9/6/3-3E6	9±0.2	6±0.2	3±0.15	5.17	102	22.9	4.44	2435
TC9.5/4.8/3.2-3E6	9.5±0.35	4.75±0.15	3.2±0.15	2.83	151	20.7	7.3	4390
TL10/6/4-3E6	10.25±0.4	5.75±0.3	4.25±0.3	3.07	188	24.1	7.8	4085
TX13/7.1/4.8-3E6	12.95±0.25	6.85±0.25	5±0.15	2.28	381	29.5	12.3	5400
TL13/7.5/5-3E6	12.75±0.4	7.25±0.35	5.25±0.3	2.46	368	30.1	12.2	5095
TX13/7.9/6.4-3E6	12.95±0.25	7.65±0.25	6.6±0.25	2.09	465	31.2	14.9	5900
TL14/9/5-3E6	14.25±0.4	8.75±0.35	5.25±0.3	2.84	430	35	12.3	4415
TL14/9/9-3E6	14.25±0.4	8.75±0.35	9.25±0.4	1.58	774	35	22.1	7955
TX16/9.1/4.7-3E6	16.13±0.13	8.82±0.18	4.95±0.13	2.527	547	37.2	14.72	5200
TL16/9.6/6.3-3E6	16.25±0.5	9.3±0.4	6.55±0.4	1.95	760	38.5	19.7	6430
TL20/10/7-3E6	20.25±0.6	9.78±0.4	7.25±0.45	1.3	1465	43.6	33.6	9685
TX22/14/6.4-3E6	22.35±0.43	13.47±0.3	6.6±0.25	2.185	1346	54.18	24.8	6000
TL22/14/13-3E6	22.35±0.7	13.47±0.3	12.95±0.6	1.064	2756	54.18	50.9	12080
TX22/14/13-3E6	22.35±0.43	13.47±0.3	12.95±0.25	1.064	2756	54.18	50.9	12080
TL25/15/10-3E6	25.25±0.7	14.75±0.6	10.25	1.23	2944	602	48.9	10200
TL29/19/7.5-3E6	29.25±0.7	18.75±0.6	7.75±0.5	1.98	2704	73.2	36.9	6340
TL29/19/15-3E6	29.25±0.7	18.75±0.6	15.45±0.6	0.978	5481	73.2	74.9	12850
TX36/23/10-3E6	36.25±0.7	22.75±0.5	10.42±0.25	1.451	5538	89.7	61.8	9090
TL36/23/15-3E6	36.25±0.9	22.75±0.7	15.25±0.6	0.935	8596	89.6	95.9	13400
TX36/23/15-3E6	36.25±0.7	22.75±0.5	15.5±0.38	0.953	8439	89.7	94.1	13600
T50/30/19-3E6	50±1	30±0.7	19±0.5	0.65	22378	120.4	186	19400
TX51/32/19-3E6	51.05±1.2	31.5±0.64	19.3±0.38	0.73	21500	125	172	17300
TL74/39/13-3E6	73.91±1.52	38.61±0.76	12.95±0.51	0.774	35298	165	207	15775
T87/56/13-3E6	87±1.25	56±0.9	12.7±0.25	1.123	42133	217.5	194	11190

Coating characteristics

T: Uncoated

TC: Parylene C coating

UL94-V2, file E94133(M)
max. operating temp. 90°C
uncoloured
isolation voltage:
>1000V

TL: Lacquer coating

UL94-V2, file E45228(M)
max. operating temp. 90°C
colour: purple/white
isolation voltage:
>1000V (OD < 12mm)
>1500V (12 ≤ OD ≤ 20)
>2000V (OD > 20)

TX: Epoxy coating

UL under approval
max. operating temp. 90°C
colour: purple/white
isolation voltage:
>1000V (OD < 12mm),
>1500V (12 ≤ OD ≤ 20)
>2000V (OD > 20)

Note: Table reflects our current product range which is continually expanding

